

Heartbeat Installation

Prerequisites:

libnet-1.1.4-3.el5 (Source: <http://rpm.pbone.net>, pending addition to sl-base repos)

libtool-ltdl (Source: sl-base)

PyXML (Source: sl-base)

Install heartbeat (Source: <http://rpm.pbone.net> pending addition to sl-base repos)

```
rpm -i heartbeat-pils-2.1.4-9.el5
```

```
rpm -i heartbeat-stonith-2.1.4-9.el5
```

```
rpm -i heartbeat-debuginfo-2.1.4-9.el5
```

```
rpm -i heartbeat-2.1.4-9.el5
```

1. Configure Heartbeat. Modify the following three files:

/etc/ha.d/ha.cf – This file must be readable by root only. This file is identical on both nodes –minus differences of peer nodes (each node points to the other's public IP address).

```
logfacility local0
#logfile /var/log/ha-log
#debugfile /var/log/ha-debug
#use_logd on
udpport 694
keepalive 1 # 1 second
deadtime 10
initdead 80
ucast eth0 <IP address of the peer node in the cluster>
node <Primary node FQDN> <Secondary node FQDN>
crm no
auto_failback no
```

/etc/ha.d/authkeys – This file must be readable by root only
Run the following script to generate the authfile

```
cat <<- !AUTH > /etc/ha.d/authkeys
    # Automatically generated authkeys file
    auth 1
    1 sha1 `dd if=/dev/urandom count=4 2>/dev/null | md5sum | cut -c1-32`
!AUTH
```

Make sure you migrate this file to all of the nodes within this cluster.

/etc/ha.d/haresources: Of the numerous possible configurations, we are currently using three configurations. First

```
fgt1x5.fnal.gov drbddisk::disk0 Filesystem::/dev/drbd0::/var/myproxy::ext3 131.225.80.233
```

Hostname	Resource	Resource Name	Type of Resource	device	directory	FS Type	Service IP
----------	----------	---------------	------------------	--------	-----------	---------	------------

Hostname: Designates the hostname where the service will primarily reside.

Resource: The type of resource that is heartbeat recognizes. Must have a correlating file in /etc/ha.d/resource.d

Resource Name: Actual name of the resource as defined by drbd in this instance

Type of Resource: The type of resource actually used

Device: The device used by the resource

Directory: Mount point of the resource

Filesystem Type: Type of filesystem

Service IP: IP address of the resource. This address follows the resource wherever it is running.

Sample implementation of a service and a service IP

```
gr11x2.fnal.gov 131.225.107.100 hb-gratia
  Hostname      Service IP      Service Name
```

Hostname: Designates the hostname where the service will primarily reside.

Service IP: IP address of the resource. This address follows the resource wherever it is running.

Service Name: The name of the service that heartbeat will handle. (NOTE: The startup script must live in either /etc/ha.d/resource.d or /etc/init.d)

Sample configuration using a service IP only

```
gr11x5.fnal.gov IPaddr::131.225.107.79/24
  Hostname      Type of      Service IP
                Resource
```

Hostname: Designates the hostname where the service will primarily reside.

Type of Resource: The type of resource controlled by heartbeat (NOTE: The types of resources are also determined by the scripts located in /etc/ha.d/resource.d)

Service IP: IP address of the resource. This address follows the resource wherever it is running.

2. Configure heartbeat service to startup on boot.
chkconfig heartbeat on
- 3 Start the heartbeat service
service heartbeat start